

# DATA SHEET




## S6EXK0005-292

BEAMEXPANDER  
MAGNIFICATION 0.5  
FOR 515 - 545 nm  
FUSED SILICA



### OUTLINE DRAWING




# DATA SHEET




## SPECIFICATIONS

article number	S6EXK0005-292
design wavelength [nm]	532
magnification factor	0.5
divergence adjustable	yes
optical principle	Galilei (no internal focus)
pointing stability [mrad]	< 1
clear input aperture [mm]	12.0
clear output aperture [mm]	12.0
recommended beam-Ø [mm] <sup>1)</sup>	10.0
total number of lenses	2
total transmission [%]	> 99
lens material	fused silica
LIDT (coating) [J/cm <sup>2</sup> ]	2.5 J/cm <sup>2</sup> per 1ns pulse at 50Hz
SP and USP usable	yes
SP and USP usable, reversed usage	yes
mounting thread	M30x1
weight [kg]	0.3
accessory	S6MEC0127 - adapter M30x1 to C-mount

## DIVERGENCE ADJUSTMENT



## MOUNTING POSITIONS



## REMARKS

<sup>1)</sup> clipped at $1/e^2$ ; wavefront error on axis (PV) < $\lambda/10$ (value provided by design)
magnification (reversed mode) = 1 / magnification (regular mode)
divergence adjustment = 0 → collimated input beam results in collimated output beam
maximum divergence adjustment is $\pm 3$ mm
RoHS compliant
length at divergence setting „0“ stated in the drawing - length extension of max. 3 mm is possible

## BACK REFLECTION POSITION

back reflections [mm]	
30.7	
back reflections reverse [mm]	
24.88	
0.00	
0.00	